

## Technical Data

(The Given data is for consideration and  
Can vary depending on environment,  
Viscosities, transferred and so on).

Model	Displacement		Suction		Discharge		Max RPM	Max Cap@ 960 RPM M3/hr.  (In water emulsion@1cps)
	Liters/rev	Liters/100rev	mm	Inch	mm	Inch		
MSE 01	0.065	6.5	24	1"	24	1"	960	6.24
MSE 01 (E)	0.065	6.5	34	1.5"	34	1.5"	960	6.54
MSE 02	0.10	10	34	1.5"	34	1.5"	960	9.6
MSE 02 (E)	0.11	11	45	2"	45	2"	960	10.56
MSE02 (E1)	0.13	13	45	2"	34	1.5"	960	12.48
ALS 66	0.17	17	38	1.5"	38	1.5"	720	12.24
ALS66 (E)	0.20	20	45	2"	45	2"	720	14.40
ALS 66 (E1)	0.23	23	45	2"	38	1.5"	720	16.56
ALS 66 (E2)	0.24	24	63	2.5"	45	2"	720	17.28
ALS 76	0.28	28	50	2"	50	2"	720	20.16
ALS76 (E)	0.31	31	63	2.5"	63	2.5"	720	22.32
ALS76 (E1)	0.34	34	63	2.5"	50	2"	720	24.48